



## MHD-230/RD

Order No.: 10.3430

**EUR 57,90**

RRP \*

### PRODUCTINFOS

#### Horn Tweeters

High-quality workmanship, with robust plastic horns, mainly made of ABS, in some cases glass fibre reinforced.

#### PA horn tweeter, 40 W, 8 $\Omega$

- Round horn of perfect workmanship
- Extra high efficiency
- Excellent radiation
- Suitable for any DJ and PA application up to professional use
- Replacement voice coil MHD-230/VC is available at option

## TECHNICAL SPECIFICATIONS

### MHD-230/RD

Impedance (Z)	8 $\Omega$
Operating voltage	-
Frequency range	fx-16000 kHz
Resonant frequency (fs)	1100 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	4000 Hz
Power rating	40 W
Peak music power output	80 W
Sensitivity	109 dB/W/m
Max. rated SPL	-
Max. voltage	-
Radiation angle, horizontal	-
Radiation angle, vertical	-
Suspension compl. (Cms)	-
Moving mass (Mms)	-
Mech. Q factor (Qms)	-
Electr. Q factor (Qes)	-
Total Q factor (Qts)	-
Equivalent volume (Vas)	-
DC resistance (Re)	-
Force factor (BxL)	-
Voice coil induct. (Le)	-
Voice coil diameter	Ø25 mm
Voice coil former	-
Linear excursion (X <sub>MAX</sub> )	-
Eff. cone area (Sd)	-
Magnet weight	-
Magnet diameter	Ø80 mm
Mounting cutout	Ø90 mm
Mounting depth	120 mm
Mounting hole diameter	104,6 mm
Hole spacing X-axis	-
Hole spacing Y-axis	-
Dimensions	Ø120 mm
Outside diameter	Ø120 mm
Width	Ø120 mm

**MHD-230/RD**

Height	-
Depth	120 mm
Protective class	-
Admiss. ambient temp.	0-40 °C
Weight	0,9 kg
Sales unit	1
Type of speaker	-

\* **Important Notice:** The retail prices shown here are non-binding recommendations that retailers can charge their customers. They are not part of any specific offer or advertisement. These prices include all charges as well as VAT, but do not cover any additional delivery and shipping costs. Our latest price lists for the retail market include all applicable delivery and payment terms for retailers.